



Thread	O/A Length (inc. Cap)		Max Probe (dia)	Product Types
	Standard	Extended		
8mm (1/4in) BSPT	38mm	75mm	4mm	ST8, ST8SS, EX8, EX8SS
15mm (1/2in) BSPT	41mm	77mm	4mm	ST15, ST15SS, EX15, EX15SS

- The extended plugs give approximately an extra 38mm (1 1/2in) for insulation.
- Other lengths available to order. Add to type number in mm.
- Standard Construction Types ST8, EX8, ST15, EX15.
- Stainless Steel Construction Types ST8SS, EX8SS, ST15SS, EX15SS.

Technical Specification	
Maximum Pressure	35bar, 500PSI.
Temp range	-8 to +135°C (18 to 275°F).
<i>Suitable for low temperature hot water, chilled water and low pressure steam.</i>	

Materials of Construction	
Body, cap and retaining ring	Brass
Cap seal	Neoprene Rubber
Retaining strap	Ethylene Propylene Rubber
Core	Ethylene Propylene Rubber

Safety

Test Plugs and accessories are not recommended to be used on medium or high temperature hot water systems. Ethylene Propylene rubber is suitable for temperatures up to 135°C however if Plugs are used with hazardous liquids or gases, protective clothing i.e. long sleeved gloves, face and eye protection should be worn.