

PHE AV3-15 H

PED Classification (2014/68/EU): SEP [FGP2NV] [FGS2NV]

THERMAL DATA				DESIGN DATA				
Primary: WATER		Secondary: WATER		Max. temperature	[°C]	-10/100		
Inlet Temperature	[°C]	75	Inlet Temperature	[°C]	25	Design pressure	[bar]	10
Outlet Temperature	[°C]	50	Outlet Temperature	[°C]	55	Test pressure	[bar]	14,3
Flowrate	[kg/h]	2587,06	Flowrate	[kg/h]	2155,05	DTML	[°C]	22,41
Pressure drop	[kPa]	10,54	Pressure drop	[kPa]	8,15	Capacity	[kW]	75
						Exchanging surface	[m ²]	0,546
Primary volume	[l]	0,66	Secondary volume	[l]	0,66	K service	[W/m ² °C]	6045,54
No. series pass hot side	[]	1	No. series pass cold side	[]	1	K Clean	[W/m ² °C]	6045,54
No. parall. pass hot side	[]	7	No. parall. pass cold side	[]	7	Oversurfacing	[%]	0

50006002002020150001

CONSTRUCTIVE DATA			DIMENSIONS					
Plates thickness	[mm]	0,5	C (width)	[mm]	198	D (horizontal interaxis)	[mm]	70
Empty weight	[kg]	21,95	A (height)	[mm]	469	B (vertical interaxis)	[mm]	381
Full weight	[kg]	23,68	F (depth)	[mm]	105	H (tightening)	[mm]	42
			G (connection dimensions)	[]	1 ¼"			
			E (connection height)	[mm]	39			

MATERIALS	
Frame	P355NH
Plates	AISI316
Gaskets	EPDM
Primary connections	AISI304
Secondary connections	AISI304
Tightening bolts	A193B7

27/04/2020

