

# PHE AV3-27 H

PED Classification (2014/68/EU): SEP [FGP2NV] [FGS2NV]

THERMAL DATA				DESIGN DATA				
Primary: WATER		Secondary: WATER		Max. temperature	[°C]	-10/100		
Inlet Temperature	[°C]	75	Inlet Temperature	[°C]	25	Design pressure	[bar]	10
Outlet Temperature	[°C]	50	Outlet Temperature	[°C]	55	Test pressure	[bar]	14,3
Flowrate	[kg/h]	5174,12	Flowrate	[kg/h]	4310,09	DTML	[°C]	22,41
Pressure drop	[kPa]	13,19	Pressure drop	[kPa]	10,1	Capacity	[kW]	150
						Exchanging surface	[m²]	1,05
Primary volume	[l]	1,24	Secondary volume	[l]	1,24	K service	[W/m² °C]	6274,69
No. series pass hot side	[ ]	1	No. series pass cold side	[ ]	1	K Clean	[W/m² °C]	6274,69
No. parall. pass hot side	[ ]	13	No. parall. pass cold side	[ ]	13	Oversurfacing	[ %]	0

50008002002020270001

CONSTRUCTIVE DATA			DIMENSIONS					
Plates thickness	[mm]	0,5	C (width)	[mm]	198	D (horizontal interaxis)	[mm]	70
Empty weight	[kg]	25,89	A (height)	[mm]	469	B (vertical interaxis)	[mm]	381
Full weight	[kg]	28,76	F (depth)	[mm]	190	H (tightening)	[mm]	75,6
			G (connection dimensions)	[ ]	1 ¼"			
			E (connection height)	[mm]	39			

MATERIALS	
Frame	P355NH
Plates	AISI316
Gaskets	EPDM
Primary connections	AISI304
Secondary connections	AISI304
Tightening bolts	A193B7

27/04/2020

