

PHE AX11-35 HL 4

PED Classification (2014/68/EU): SEP [FGP2NV] [FGS2NV]

THERMAL DATA						DESIGN DATA			
Primary: WATER			Secondary: WATER			Max. temperature		[°C]	-10/100
Inlet Temperature			[°C]	80	Inlet Temperature		[°C]	55	
Outlet Temperature			[°C]	60	Outlet Temperature		[°C]	75	
Flowrate			[kg/h]	25851,74	Flowrate		[kg/h]	25865,56	
Pressure drop			[kPa]	47,99	Pressure drop		[kPa]	48,92	
Primary volume			[l]	7,4	Secondary volume		[l]	7,4	
No. series pass hot side			[]	1	No. series pass cold side		[]	1	
No. parall. pass hot side			[]	17	No. parall.pass cold side		[]	17	
50131041045420350041									

CONSTRUCTIVE DATA			DIMENSIONS					
Plates thickness	[mm]	0,5	C (width)	[mm]	320	D (horizontal interaxis)	[mm]	140
Empty weight	[kg]	148,5	A (height)	[mm]	1291	B (vertical interaxis)	[mm]	1036
Full weight	[kg]	165,29	F (depth)	[mm]	430	H (tightening)	[mm]	87,5
MATERIALS			G (connection dimensions)		[]	2 ½"		
			E (connection height)		[mm]	165		

MATERIALS	
Frame	P355NH
Plates	AISI304
Gaskets	EPDM
Primary connections	AISI304
Secondary connections	AISI304
Tightening bolts	A193B7

25/07/2019

