

PHE AX11-43 HL 4

PED Classification (2014/68/EU): SEP [FGP2NV] [FGS2NV]

THERMAL DATA				DESIGN DATA				
Primary: WATER			Secondary: WATER			Max. temperature	[°C]	-10/100
Inlet Temperature	[°C]	80	Inlet Temperature	[°C]	55	Design pressure	[bar]	6
Outlet Temperature	[°C]	60	Outlet Temperature	[°C]	75	Test pressure	[bar]	8,58
Flowrate	[kg/h]	34468,99	Flowrate	[kg/h]	34487,42	DTML	[°C]	5
Pressure drop	[kPa]	54,68	Pressure drop	[kPa]	55,75	Capacity	[kW]	800
Primary volume			Secondary volume					
No. series pass hot side	[]	1	No. series pass cold side	[]	1			
No. parall. pass hot side	[]	21	No. parall.pass cold side	[]	21			
						50131041045420430041		

CONSTRUCTIVE DATA			DIMENSIONS					
Plates thickness	[mm]	0,5	C (width)	[mm]	320	D (horizontal interaxis)	[mm]	140
Empty weight	[kg]	157,78	A (height)	[mm]	1291	B (vertical interaxis)	[mm]	1036
Full weight	[kg]	178,05	F (depth)	[mm]	430	H (tightening)	[mm]	107,5
MATERIALS			G (connection dimensions)	[]	2 ½"	25/07/2019		
			E (connection height)	[mm]	165			
Frame	P355NH							
Plates	AISI304							
Gaskets	EPDM							
Primary connections	AISI304							
Seconday connections	AISI304							
Tightening bolts	A193B7							

