

PHE AX11-87 HL 14

PED Classification (2014/68/EU): SEP [FGP2NV] [FGS2NV]

THERMAL DATA				DESIGN DATA				
Primary: WATER			Secondary: WATER			Max. temperature	[°C]	-10/100
Inlet Temperature	[°C]	80	Inlet Temperature	[°C]	55	Design pressure	[bar]	6
Outlet Temperature	[°C]	60	Outlet Temperature	[°C]	75	Test pressure	[bar]	8,58
Flowrate	[kg/h]	64629,36	Flowrate	[kg/h]	64663,91	DTML	[°C]	5
Pressure drop	[kPa]	58,82	Pressure drop	[kPa]	59,74	Capacity	[kW]	1500
Primary volume			Secondary volume					
No. series pass hot side	[l]	18,7	No. series pass cold side	[l]	18,7			
No. parall. pass hot side	[]	1	No. parall. pass cold side	[]	1			
No. parall. pass hot side	[]	43	No. parall. pass cold side	[]	43			
						50134041045420870141		

CONSTRUCTIVE DATA			DIMENSIONS					
Plates thickness	[mm]	0,5	C (width)	[mm]	320	D (horizontal interaxis)	[mm]	140
Empty weight	[kg]	216,52	A (height)	[mm]	1291	B (vertical interaxis)	[mm]	1036
Full weight	[kg]	255,93	F (depth)	[mm]	650	H (tightening)	[mm]	217,5
MATERIALS			G (connection dimensions)	[]	2 ½"			
			E (connection height)	[mm]	165			

MATERIALS	
Frame	P355NH
Plates	AISI304
Gaskets	EPDM
Primary connections	AISI304
Secondary connections	AISI304
Tightening bolts	A193B7

25/07/2019

