

PHE AV40-67 HL 58

PED Classification (2014/68/EU): SEP [FGP2NV] [FGS2NV]

THERMAL DATA				DESIGN DATA					
Primary: WATER			Secondary: WATER			Max. temperature	[°C]	-10/100	
Inlet Temperature	[°C]	80	Inlet Temperature	[°C]	55	Design pressure	[bar]	6	
Outlet Temperature	[°C]	60	Outlet Temperature	[°C]	75	Test pressure	[bar]	8,58	
Flowrate	[kg/h]	64629,36	Flowrate	[kg/h]	64663,91	DTML	[°C]	5	
Pressure drop	[kPa]	46,97	Pressure drop	[kPa]	46,82	Capacity	[kW]	1500	
						Exchanging surface	[m²]	29,315	
Primary volume			[l]	34,52	Secondary volume			[l]	34,52
No. series pass hot side			[]	1	No. series pass cold side			[]	1
No. parall. pass hot side			[]	33	No. parall.pass cold side			[]	33
50191071075720670581									

CONSTRUCTIVE DATA			DIMENSIONS		
Plates thickness	[mm]	0,5	C (width)	[mm]	613
Empty weight	[kg]	474,66	A (height)	[mm]	1413
Full weight	[kg]	551,7	F (depth)	[mm]	743
			G (connection dimensions)	[]	DN 150
			E (connection height)	[mm]	275
			D (horizontal interaxis)	[mm]	296
			B (vertical interaxis)	[mm]	890
			H (tightening)	[mm]	207,7

MATERIALS	
Frame	P355NH
Plates	AISI304
Gaskets	EPDM
Primary connections	P355NH
Secondary connections	P355NH
Tightening bolts	A193B7

08/04/2020

