

PHE AV3-35 H

PED Classification (2014/68/EU): SEP [FGP2NV] [FGS2NV]

THERMAL DATA						DESIGN DATA		
Primary: WATER			Secondary: WATER			Max. temperature	[°C]	-10/100
Inlet Temperature	[°C]	75	Inlet Temperature	[°C]	10	Design pressure	[bar]	10
Outlet Temperature	[°C]	40	Outlet Temperature	[°C]	50	Test pressure	[bar]	14,3
Flowrate	[kg/h]	4928,96	Flowrate	[kg/h]	4304	DTML	[°C]	27,42
Pressure drop	[kPa]	8,15	Pressure drop	[kPa]	6,9	Capacity	[kW]	200
						Exchanging surface	[m²]	1,386
Primary volume	[l]	1,62	Secondary volume	[l]	1,62	K service	[W/m²°C]	5180,89
No. series pass hot side	[]	1	No. series pass cold side	[]	1	K Clean	[W/m²°C]	5180,89
No. parall. pass hot side	[]	17	No. parall.pass cold side	[]	17	Oversurfacing	[%]	0
						50009002002020350001		

CONSTRUCTIVE DATA			DIMENSIONS					
Plates thickness	[mm]	0,5	C (width)	[mm]	198	D (horizontal interaxis)	[mm]	70
Empty weight	[kg]	28,35	A (height)	[mm]	469	B (vertical interaxis)	[mm]	381
Full weight	[kg]	31,98	F (depth)	[mm]	240	H (tightening)	[mm]	98
MATERIALS			G (connection dimensions)		[]	1 ¼"		
			E (connection height)		[mm]	39		

MATERIALS	
Frame	P355NH
Plates	AISI316
Gaskets	EPDM
Primary connections	AISI304
Secondary connections	AISI304
Tightening bolts	A193B7

27/04/2020

