

Receiver

From

Company
Reference
Address
Phone
Fax
E-mail

Item n° : **Customer pos. no.:**

60151011

Model :

EVOPLUS D 100/280.50 M

Pump data

Pressure rating : 1,6 MPa
Min. fluid temperature : -10 °C
Max fluid temperature : 110 °C
EEI : ≤ 0,20

Minimum suction head :

Temperature °C 90 - 100
Minimum suction head : m 20 - 25

Requested data

Flow :
Head :
Fluid (%) :
Fluid Temperature : 20 °C
Density : 998,3 kg/m³
Kinematic viscosity : 1,005 mm²/s
Vapor pressure : 0,00 MPa

Hydraulic data (duty point)



Flow :
Head :

Materials

Pump body Cast iron 250 UNI ISO 185 - CTF
Impeller Technopolymer
Motor shaft Stainless steel
Seal ring EPDM
Motor casing Die cast aluminium
Closing flange Stainless steel
Thrust ring support Stainless steel

Curve tolerance according to ISO 9906

Number of working motors : 2





PERFORMANCE CURVES

2024-11-05

Page 2 / 3

DAB PUMPS S.p.A.
Via Marco Polo, 14 - 35035 Mestrino (PD), Italy
Tel. +39 049 5125000 - Fax +39 049 5125950
www.dabpumps.com

Receiver


From

Company
Reference
Address
Phone
Fax
E-mail

EVOPLUS D 100/280.50 M

Number of working motors : 2

Curve tolerance according to ISO 9906



Suction side :

DN 50

PN6, PN10, PN16

Discharge side :

DN 50

PN6, PN10, PN16

Flow :

Head :

Rated speed :

2.900 1/min

MAIN_PROJECT_TITLE

BUSINESS_PROCESS_ID

OWNER_

ISSUE_DATE

2024-11-05



DIMENSIONAL DRAWING

2024-11-05

Page 3 / 3


DAB PUMPS S.p.A.
Via Marco Polo, 14 - 35035 Mestrino (PD), Italy
Tel. +39 049 5125000 - Fax +39 049 5125950
www.dabpumps.com

Receiver

From

Company
Reference
Address
Phone
Fax
E-mail

EVOPLUS D 100/280.50 M



Dimensions in mm

Pump connection

1	A1	19	H1	480				
2	A2	14	H2	273				
3	B	400	H3	235				Suction
4	B1	75	H4	232				DN 50
5	B2	325	I	130				PN6, PN10, PN16
6	D	165	I1	130				
7	D1	125	I2	125				Discharge
8	D2	110	I3	50				DN 50
9	D3	99	L	280				PN6, PN10, PN16
10	D4	53	M	M12				
11	H	467						

MAIN_PROJECT_TITLE

BUSINESS_PROCESS_ID

OWNER_

ISSUE_DATE

2024-11-05